



GPS  
GSM  
SMS  
RFID  
BASED  
TRACKING  
MONITORING  
SOLUTIONS

High on Features  
Low on Price



**CERTIFICATIONS:**



**S101**

**Ruggedized IP67 Enclosure**

**U101V1**

Parameters	Description
GSM Module	Quad Band GSM, GPRS: class 10 / 12
GPS Module	66 acquisition-/ 22 tracking channels, Ultra high tracking/navigation sensitivity: -165dBm1
Antennas	GSM-GPS Internal Antenna
Communication Interface	TCP/IP on GPRS.
Record Storage/Buffer	5000 Tracking Records.
Ports/Interface	1-USB Device type, 1 Analog I/O and 2 Digital I/O, 1 Ignition ,1 Voice channel (optional)
Speed Sensor	GPS(default)
Motion Sensor	NA
LED Indication	Processing, GSM, GPS, USB Detection
Connectors	6 Pin power mate connector
Power Supply	Wide DC input voltage range (9V - 32V),
Internal Battery	1500mah, 5 to 8 Hr backup,
Enclosure	ABS Plastic Casing IP67
Temperature	Operating: -10°C to +55°C Storage: -10°C to +85°C
Dimension (mm x mm x mm)	98L x 73.1 W x 25 H in mm
Weight	160 grams

Parameters	Description
GSM Module	Quad Band GSM, GPRS: class 10 / 12
GPS Module	66 acquisition-/ 22 tracking channels, Ultra high tracking/navigation sensitivity: -165dBm1
Antennas	GSM-GPS Internal Antenna
Communication Interface	TCP/IP on GPRS.
Record Storage/Buffer	20000 Tracking Records.
Ports/Interface	1-USB Device type, 1 Analog I/O and 2 Digital I/O 1 Ignition, 1 Voice Channel, Serial Port
Speed Sensor	Real time(optional), GPS(default)
Motion Sensor	Accelerometer
LED Indication	Processing, GSM, GPS, USB Detection
Connectors	8 Pin power mate connector
Power Supply	Wide DC input voltage range (9V - 32V),
Internal Battery	1500mah, 5 to 8 Hr backup,
Enclosure	ABS Plastic Casing IP67
Temperature	Operating: -10°C to +55°C Storage: -10°C to +85°C
Dimension (mm x mm x mm)	115 L x 80 W x 25 H in mm
Weight	165 grams

**iTriangle Advantage**

**Supported Accessories**

- Standalone, Plug and play, Compact Tracking Device
- Advanced Power Management with Internal Battery
- Comprehensive Fleet Management Capabilities
- Driving Behavior Management
- Remote Monitoring, Control and Diagnostics of Equipment
- Data collection and Voice Communication
- Analog and Digital Sensor Support
- Ruggedized IP67 Enclosure



RFID



Voice Kit



Emergency Button



Temporator Sensor



Door Sensor



Immobilizar



AC Status

& much more.....

Note: We pursue a policy of continuous research product development. Specifications & Features are subjected to change without notice

Design  
Development  
Manufacturing  
& Software  
Services

For more information:  
Contact: +91 9739221001  
+91 9739974445  
or, write to us at:  
customer@itriangle.in

An ISO 9001:2008 Certified Company



innovate • optimise • deliver

www.itriangle.in